

RAZ- AP 600 / RAZ- SP 600

SPECIFICATION	RAZ-AP600	RAZ-SP600
WEIGHT CAPACITY	600 lbs.	600 lbs.
FRAME WIDTH	22"	22"
SEAT WIDTH	23"	23"
SEAT DEPTH ADJUSTMENT	18" – 20"	18" – 20"
CENTER OF GRAVITY ADJUSTMENT	Back Position: Up to 1" fore/aft	Wheel Axle: Up to 1½" fore/aft Back Position: Up to 1" fore/aft
SEAT HEIGHT (Seat To Floor) Standard 5" Caster: Optional 6" Caster:	19¼", 20¼", 21¼", 22¼", 23¼" 20¼", 21¼", 22¼", 23¼", 24¼"	20¼", 21¼", 23¼" 20¼", 21¼", 23¼"
CLEARANCE HEIGHT 5" Caster (under pan bracket): 5" Caster (under frame): 6" Caster (under pan bracket): 6" Caster (under frame):	14", 15", 16", 17", 18" 15½", 16½", 17½", 18½", 19½" 15", 16", 17", 18", 19" 16½", 17½", 18½", 19½", 20½"	15", 16", 18" 16½", 17½", 19½" 15", 16", 18" 16½", 17½", 19½"
BACK HEIGHT	20"	20"
BACK ANGLE	95°, 100°	95°, 100°
ARMREST HEIGHT	8"	8"
WIDTH BETWEEN ARMPADS	22½"	22½"
LATERAL SUPPORT (adjustment range)	1¼" - 2½" offset 1" fore/aft ±5° pad angle	1¼" - 2½" offset 1" fore/aft ±5° pad angle
FOOTREST ADJUSTMENT (seat to footplate)	16"-20½" (Z709) 18"-22½" (Z711)	16"-20½" (Z709) 18"-22½" (Z711)
STANDARD CASTER: OPTIONAL CASTER:	Dual-locking 5" casters (x4) Dual-locking 6" casters (x4)	Dual-locking 5" casters (x2) Dual-locking 6" casters (x2)
REAR WHEELS (with molded handrims)	Optional Retrofit Kit (Z618)	24" Wheels
OVERALL WIDTH	26" (w/ standard armpad) 29½" (w/ Z715 armpad)	30" (outside handrim)
OVERALL LENGTH (with footrests)	39" - 40½"	44" - 45¼"
OVERALL LENGTH (without footrests)	29½"	32" - 34½"
PRODUCT WEIGHT	54 lbs. (w/ 5" casters) 56 lbs. (w/ 6" casters)	68 lbs. (w/ 5" casters) 69 lbs. (w/ 6" casters)
FRAME AND HARDWARE MATERIAL	Stainless Steel	Stainless Steel